

SLG, PF, SG Prefill Valves

How to order



SG	24	A2	-
Series	Valve size	Opening pressure	Connection type
SG: Two position 180°	16 24	A1: Light A2: Heavy	-: SG: SLG type
SLG: Two position 90°	32 48		-: Without flang
PF- New type	80 125 90 150 100		FP: with P port flang FT: with T port flang F: with P.T port flang

Specification

Model			Max. operated pressure (kgf/cm ²)	Using flow (L/min)			Opening pressure (kgf/cm ²)	Conn-ecting PT	Weight (kg)		
90°	180°	New type		SG, SLG		PF			SG, SLG	PF	PF-***20
				Vacuum self-priming	Using PI						
-	SG-16	PF-50	250	260+100m	400+100m	250	0.12	2"	30.0	2.0	3.5
SLG-24	SG-24	PF-80	250	600+150m	900+150m	400	0.14	3"	52.0	2.8	8.9
-	-	PF-90	250	-	-	630	0.14	3 1/2"	-	3.8	12.4
SLG-32	SG-32	PF-100	250	1100+300m	1600+300m	1000	0.16	4"	100.0	6.0	16.5
-	-	PF-125	250	-	-	1600	0.16	5"	-	10.8	26.8
SLG-48	SG-48	PF-150	250	2200+600m	3200+600m	2500	0.16	6"	240.0	23.5	42.6

Symbol

